

# BLOQ CARPET TILES - SPECIFICATION TEXT

**BLOQ**  
creative  
carpet tiles

## 1. GENERAL INFORMATION

**MANUFACTURER** BLOQ creative carpet tiles

**PRODUCT NAME** Grain

## 2. PRODUCT DESCRIPTION

The carpet tile is GUT certified and conforms to the EN 1307 classification. The carpet tile is suitable for intensive use and is therefore suitable for wheelchairs.

The pile weight of the carpet tile is approximately 650 g/m<sup>2</sup>. The carpet tile is stabilised by a bitumen backing, the finish of which consists of modified bitumen with the addition of thermoplastic elastomers. The backing contains at least 70% recycled material. The carpet tile also has a glass fibre fleece that gives better dimensional stability ( $\leq 0,2\%$ ).

The pile material consists of 100% polyamide fibre type 6 from Aquafil and is Solution Dyed. This type of yarn means better colour fastness and the best result against light and water.

The carpet tile has a tufted loop pile. The pattern is two-toned and is inspired by waving fields of grain and grasses.

The collection consists of 18 colours.

The production and finishing of this carpet tile takes place in the Netherlands by an ISO 9001 certified manufacturer.

## 3. TECHNICAL SPECIFICATIONS

<b>TYPE OF MANUFACTURE</b>	Tufted loop pile with pattern 1/10"
<b>PILE FIBER COMPOSITION</b>	100% Polyamide 6 Solution Dyed Nylon from Aquafil
<b>BACKING</b>	Bitback, modified bitumen – 70% recycled content.
<b>DIMENSION</b>	25 X 100 cm
<b>PILE WEIGHT</b>	650 g/m <sup>2</sup>
<b>TOTAL WEIGHT</b>	4 400 g/m <sup>2</sup>
<b>TOTAL THICKNESS</b>	6,9 mm
<b>CLASSIFICATION</b>	Class 33 – EN 1307
<b>CASTOR CHAIR RATING</b>	EN 985 I A: intensive use
<b>FIRE CLASSIFICATION</b>	EN 13501-1 I B <sub>fl</sub> – s1
<b>IMPACT SOUND INSULATION</b>	EN ISO 10140-3 I $\Delta L_w$ 26 dB
<b>PERMANENT ANTISTATIC</b>	ISO 6365 I $\leq 2$ kV
<b>THERMAL RESISTANCE</b>	ISO 10965 I $\leq 1 \times 10^9$ Ohm
<b>COLOUR FASTNESS TO LIGHT</b>	EN ISO 105-B02 I $\geq 7$

## 4. CERTIFICATES

<b>WARRENTY</b>	15 years
<b>GUT</b>	The product fulfils the GUT criteria. The GUT licence number is: 6DFDDB9E. Only textile floor coverings that have been tested by recognized European research institutes for harmful substances, emissions and odour formation are given a licence number.