BLOQ CARPET TILES - SPECIFICATION TEXT



1. GENERAL INFORMATION

MANUFACTURERBLOQ creative carpet tilePRODUCT NAMEPositive & Negative

2. PRODUCT DESCRIPTION

The carpet tile is GUT certified and conforms to the EN 1307 classification. The carpet tile is suitable for intensive use and is also suitable for wheelchairs.

The pile weight of the carpet tile is approximately 750 g/m2. The carpet tile is stabilised by a bitumen backing, the finish of which consists of modified bitumen with the addition of thermoplastic elastomers. The backing contains at least 70% recycled material. The carpet tile also has a glass fibre fleece that gives better dimensional stability (\leq 0.2%).

The pile material consists of 100% polyamide fibre type 6 from Aquafil and is Solution Dyed. This type of yarn means better colour fastness and the best result against light and water.

The carpet tile has a tufted loop pile. The design is inspired by the bark of a tree - a playful yet elegant combo of light and dark. POSITIVE adds a ligt touch, filling the room with a tranquil vide.

The collection is composed of 8 soft pastel colours in two opposite shades: POSITIVE and NEGATIVE. POSITIVE is made up of a light and neutral background, detailed with darker, saturated threads.

The production and finishing of these carpet tiles takes place in the Netherlands by an ISO 9001 certified manufacturer.

3. TECHNICAL SPECIFICATIONS

TYPE OF MANUFACTURE Tufted loop pile with pattern 1/10"

PILE FIBER COMPOSITION 100% Polyamide 6 Solution Dyed

Nylon from Aquafi

BACKING Bitback, modified bitumen –

70% recycled content.

DIMENSION 50 X 50 cm

PILE WEIGHT 750 g/m²

TOTAL WEIGHT 4 400 g/m²

 $\textbf{TOTAL THICKNESS} \quad 7,4 \text{ mm}$

CLASSIFICATION Class 33 – EN 1307

CASTOR CHAIR RATING EN 985 | A: intensive use

FIRE CLASSIFICATION EN 13501-1 | Bfl – s1

 $\textbf{IMPACT SOUND INSULATION} \quad \text{EN ISO } 10140\text{--}3 \text{ I } \Delta \text{LW } 28 \text{ dB}$

 $\textbf{PERMANENT ANTISTATIC} \quad \text{ISO } 6365 \text{ I} \leq 2 \text{ kV}$

THERMAL RESISTANCE ISO $10965 \mid \le 1 \text{ X } 10^9 \text{ Ohm}$ COLOUR FASTNESS TO LIGHT EN ISO $105\text{-}B02 \mid \ge 7$

4. CERTIFICATES

WARRENTY 15 years

OUT The

The product fulfils the GUT criteria The GUT licence number is: BC5AB0C0.

Only textile floor coverings that have been tested by recognized European research institutes for harmful substances, emissions and odour formation are given a licence number.