

BLOQ CARPET TILES - SPECIFICATION TEXT

BLOQ
creative
carpet tiles

1. GENERAL INFORMATION

MANUFACTURER BLOQ creative carpet tiles
PRODUCT NAME Solace

2. PRODUCT DESCRIPTION

The carpet tile is GUT certified and conforms to the EN 1307 classification. The carpet tile is suitable for intensive use and is therefore suitable for wheelchairs.

The pile weight of the carpet tile is approximately 675 g/m². The carpet tile is stabilised by a bitumen backing, the finish of which consists of modified bitumen with the addition of thermoplastic elastomers. The backing contains at least 70% recycled material. The carpet tile also has a glass fibre fleece that gives better dimensional stability ($\leq 0.2\%$).

The pile material consists of 100% polyamide fibre type 6 from Aquafil and is Solution Dyed. This type of yarn means better colour fastness and the best result against light and water.

The carpet tile has a tufted loop pile. The carpet tile has a cloud-inspired design with a dreamy mood. The pattern reveals clouds in two shades: always different, always in style, always unique.

SOLACE carpet tiles are most beautiful when installed non-directional. By placing the tiles in varying directions, you get less repetition in the pattern, giving your SOLACE floor an even more natural look. On the back of each tile, you will find an arrow indicating the pile direction, making non-directional installation easier.

The collection consists of 11 colours.

The production and finishing of this carpet tile takes place in the Netherlands by an ISO 9001 certified manufacturer.

3. TECHNICAL SPECIFICATIONS

TYPE OF MANUFACTURE Tufted Patterned Loop Pile 1/10"
PILE FIBER COMPOSITION 100% Polyamide 6
Solution Dyed Nylon made by Aquafil
BACKING Bitback, Modified Bitumen
70% Recycled Content
DIMENSION 50 X 50 cm
PILE WEIGHT 675 g/m²
TOTAL WEIGHT 4 400 g/m²
TOTAL THICKNESS 6.7 mm
CLASSIFICATION EN 1307 | Class 33
CASTOR CHAIR RATING EN 985 | A: intensive use
FIRE CLASSIFICATION EN 13501-1 | B_{f1}-s1
IMPACT SOUND INSULATION EN ISO 10140-3 | ΔL_w 26 dB
PERMANENT ANTISTATIC ISO 6356 | ≤ 2 kV
TRANSVERSAL RESISTANCE ISO 10965 | $\leq 1 \times 10^9$ Ohm
COLOUR FASTNESS TO LIGHT EN ISO 105-B02 | ≥ 7

4. CERTIFICATES

WARRENTY 15 years
GUT The product fulfils the GUT criteria. The GUT licence number is: 3CE0E3FA. Only textile floor coverings that have been tested by recognized European research institutes for harmful substances, emissions and odour formation are given a licence number.